

REV.	CHANG DESCRIPTION	BY	DATE
A	NEW RELEASE	MW	25/12/10

QTY'S	CONBEONE P/N	MMQD	TOLERANCE	PROCESSING	UL CLASS
3P	CB020715-031	100	±6	39-01-4030	UL 94V-2
3P	CB020715-032	200	±6	39-01-4030	UL 94V-2
3P	CB020715-033	300	±8	39-01-4030	UL 94V-2
3P	CB020715-034	500	±10	39-01-4030	UL 94V-2
3P	CB020715-035	1000	±10	39-01-4030	UL 94V-2
3P	CB020715-036	150	±10	39-01-4030	UL 94V-2
3P	CB020715-037	700	±10	39-01-4030	UL 94V-2
3P	CB020715-131	100	±6	39-01-4031	UL 94V-0
3P	CB020715-132	200	±6	39-01-4031	UL 94V-0
3P	CB020715-133	300	±8	39-01-4031	UL 94V-0
3P	CB020715-134	500	±10	39-01-4031	UL 94V-0
3P	CB020715-135	1000	±10	39-01-4031	UL 94V-0
3P	CB020715-136	150	±10	39-01-4031	UL 94V-0
3P	CB020715-137	700	±10	39-01-4031	UL 94V-0
4P	CB020715-041	100	±6	39-01-4040	UL 94V-2
4P	CB020715-042	200	±6	39-01-4040	UL 94V-2
4P	CB020715-043	300	±8	39-01-4040	UL 94V-2
4P	CB020715-044	500	±10	39-01-4040	UL 94V-2
4P	CB020715-045	1000	±10	39-01-4040	UL 94V-2
4P	CB020715-046	150	±10	39-01-4040	UL 94V-2
4P	CB020715-047	700	±10	39-01-4040	UL 94V-2
4P	CB020715-141	100	±6	39-01-4041	UL 94V-0
4P	CB020715-142	200	±6	39-01-4041	UL 94V-0
4P	CB020715-143	300	±8	39-01-4041	UL 94V-0
4P	CB020715-144	500	±10	39-01-4041	UL 94V-0
4P	CB020715-145	1000	±10	39-01-4041	UL 94V-0
4P	CB020715-146	150	±10	39-01-4041	UL 94V-0
4P	CB020715-147	700	±10	39-01-4041	UL 94V-0
5P	CB020715-051	100	±6	39-01-4050	UL 94V-2
5P	CB020715-052	200	±6	39-01-4050	UL 94V-2
5P	CB020715-053	300	±8	39-01-4050	UL 94V-2
5P	CB020715-054	500	±10	39-01-4050	UL 94V-2
5P	CB020715-055	1000	±10	39-01-4050	UL 94V-2
5P	CB020715-056	150	±10	39-01-4050	UL 94V-2
5P	CB020715-057	700	±10	39-01-4050	UL 94V-2
5P	CB020715-151	100	±6	39-01-4051	UL 94V-0
5P	CB020715-152	200	±6	39-01-4051	UL 94V-0
5P	CB020715-153	300	±8	39-01-4051	UL 94V-0
5P	CB020715-154	500	±10	39-01-4051	UL 94V-0
5P	CB020715-155	1000	±10	39-01-4051	UL 94V-0
5P	CB020715-156	150	±10	39-01-4051	UL 94V-0
5P	CB020715-157	700	±10	39-01-4051	UL 94V-0

WIRE CHART:

3P:

SIDE A	RED	SIDE B	RED
PRINT	BLACK	PRINT	BLACK
BLK/CK	PRN.1	BLK/CK	PRN.1
PRN.2	YELLOW	PRN.2	YELLOW
PRN.3	GREEN	PRN.3	GREEN

4P:

SIDE A	RED	SIDE B	RED
PRINT	BLACK	PRINT	BLACK
BLK/CK	PRN.1	BLK/CK	PRN.1
PRN.2	YELLOW	PRN.2	YELLOW
PRN.3	GREEN	PRN.3	GREEN
PRN.4	BLUE	PRN.4	BLUE

5P:

SIDE A	RED	SIDE B	RED
PRINT	BLACK	PRINT	BLACK
BLK/CK	PRN.1	BLK/CK	PRN.1
PRN.2	YELLOW	PRN.2	YELLOW
PRN.3	GREEN	PRN.3	GREEN
PRN.4	BLUE	PRN.4	BLUE
PRN.5	ORANGE	PRN.5	ORANGE

REMARK:

- 1) ROHS 2.0 COMPLIANT.
- 2) MEET IPC-620 SPECIFICATION.
- 3) 100% OPEN/SHORT TEST.

3	AR	M	UL1061 HOOK WIRE, 300V, 18AWG, COLOR SEE TABLE
2	AR	RCS	4.2mm PITCH EVALE TERMINAL, TIN PLATED, 18-26range, MOL EX39000038
1	RCS	RCS	4.2mm PITCH REC.HSG, SMD, ROW, XXP, MOL EX3940-40XX
SN	QTY	UNIT	DESCRIPTION
GENERAL TOLERANCE:			
9 P.C. ± 127			
2 P.C. ± 0.13			
4 P.C. ± 0.02			
ANGLES 3P			
APPROVED: P/N: CONBEONE			
DRAWN: MW			
CHECKED: CT			
DOCR# SD-CB020715			
TITLE: Molex 4.2mm Mini Fit Wire Harness			
5567 Series, Dual Ends Type A, CDA-V02			
SIZE: A4			
UNIT: MM			
SCALE: N.T.S.			
PAGE: 1 OF 1			
REV: A			

