



REV.	CHANG DESCRIPTION	BY	DATE
A	NEW RELEASE	MW	240726
B	CHANGE L	MW	25/10/17



SIDE A

SIDE B

SHOWN OF 22013047

CKTS	CABLE P/N	L(MM)	Tolerance	HSG P/N
2	CB030431-021	100	±6	22-01-3027
2	CB030431-022	200	±6	22-01-3027
2	CB030431-023	300	±6	22-01-3027
2	CB030431-024	500	±8	22-01-3027
2	CB030431-025	1000	±10	22-01-3027
3	CB030431-031	100	±6	22-01-3037
3	CB030431-032	200	±6	22-01-3037
3	CB030431-033	300	±6	22-01-3037
3	CB030431-034	500	±8	22-01-3037
3	CB030431-035	1000	±10	22-01-3037
4	CB030431-041	100	±6	22-01-3047
4	CB030431-042	200	±6	22-01-3047
4	CB030431-043	300	±6	22-01-3047
4	CB030431-044	500	±8	22-01-3047
4	CB030431-045	1000	±10	22-01-3047
5	CB030431-051	100	±6	22-01-3057
5	CB030431-052	200	±6	22-01-3057
5	CB030431-053	300	±6	22-01-3057
5	CB030431-054	500	±8	22-01-3057
5	CB030431-055	1000	±10	22-01-3057
6	CB030431-061	100	±6	22-01-3067
6	CB030431-062	200	±6	22-01-3067
6	CB030431-063	300	±6	22-01-3067
6	CB030431-064	500	±8	22-01-3067
6	CB030431-065	1000	±10	22-01-3067
7	CB030431-071	100	±6	22-01-3077
7	CB030431-072	200	±6	22-01-3077
7	CB030431-073	300	±6	22-01-3077
7	CB030431-074	500	±8	22-01-3077
7	CB030431-075	1000	±10	22-01-3077
8	CB030431-081	100	±6	22-01-3087
8	CB030431-082	200	±6	22-01-3087
8	CB030431-083	300	±6	22-01-3087
8	CB030431-084	500	±8	22-01-3087
8	CB030431-085	1000	±10	22-01-3087

CKTS	CABLE P/N	L(MM)	Tolerance	HSG P/N
9	CB030431-091	100	±6	22-01-3097
9	CB030431-092	200	±6	22-01-3097
9	CB030431-093	300	±6	22-01-3097
9	CB030431-094	500	±8	22-01-3097
9	CB030431-095	1000	±10	22-01-3097
10	CB030431-101	100	±6	22-01-3107
10	CB030431-102	200	±6	22-01-3107
10	CB030431-103	300	±6	22-01-3107
10	CB030431-104	500	±8	22-01-3107
10	CB030431-105	1000	±10	22-01-3107
11	CB030431-111	100	±6	22-01-3117
11	CB030431-112	200	±6	22-01-3117
11	CB030431-113	300	±6	22-01-3117
11	CB030431-114	500	±8	22-01-3117
11	CB030431-115	1000	±10	22-01-3117
12	CB030431-121	100	±6	22-01-3127
12	CB030431-122	200	±6	22-01-3127
12	CB030431-123	300	±6	22-01-3127
12	CB030431-124	500	±8	22-01-3127
12	CB030431-125	1000	±10	22-01-3127
13	CB030431-131	100	±6	22-01-3137
13	CB030431-132	200	±6	22-01-3137
13	CB030431-133	300	±6	22-01-3137
13	CB030431-134	500	±8	22-01-3137
13	CB030431-135	1000	±10	22-01-3137
14	CB030431-141	100	±6	22-01-3147
14	CB030431-142	200	±6	22-01-3147
14	CB030431-143	300	±6	22-01-3147
14	CB030431-144	500	±8	22-01-3147
14	CB030431-145	1000	±10	22-01-3147
15	CB030431-151	100	±6	22-01-3157
15	CB030431-152	200	±6	22-01-3157
15	CB030431-153	300	±6	22-01-3157
15	CB030431-154	500	±8	22-01-3157
15	CB030431-155	1000	±10	22-01-3157

CKTS	CABLE P/N	L(MM)	Tolerance	HSG P/N
16	CB030431-161	100	±6	22-01-3167
16	CB030431-162	200	±6	22-01-3167
16	CB030431-163	300	±6	22-01-3167
16	CB030431-164	500	±8	22-01-3167
16	CB030431-165	1000	±10	22-01-3167

WIRE CHART:

SIDE A		SIDE B	Housing P/N
PIN 1	Black	PIN 1	22-01-3027
PIN 2	Black	PIN 2	22-01-3037
PIN 3	Black	PIN 3	22-01-3047
PIN 4	Black	PIN 4	22-01-3057
PIN 5	Black	PIN 5	22-01-3067
PIN 6	Black	PIN 6	22-01-3077
PIN 7	Black	PIN 7	22-01-3087
PIN 8	Black	PIN 8	22-01-3097
PIN 9	Black	PIN 9	22-01-3107
PIN 10	Black	PIN 10	22-01-3117
PIN 11	Black	PIN 11	22-01-3127
PIN 12	Black	PIN 12	22-01-3137
PIN 13	Black	PIN 13	22-01-3147
PIN 14	Black	PIN 14	22-01-3157
PIN 15	Black	PIN 15	22-01-3167
PIN 16	Black	PIN 16	22-01-3167

REMARK:

- 1) ROHS 2.0 COMPLIANT.
- 2) MEET IPC-620 SPECIFICATION.

3	AR	M	UL1061 HOOK WIRE, 80°C, 300V, BLACK, 22AWG
2	2N	PCS	2.54mm PITCH KK254 FEMALE TERMINAL, MOLEX 8500031
1	2	PCS	2.54mm PITCH KK254 FEMALE HSG, MOLEX 22-01-3xx7
S/N	Q'TY	UNIT	DESCRIPTION
			GENERAL TOLERANCE UNLESS SPECIFIED: 0 PLC ±1.27 1 PLC ±0.50 2 PLC ±0.13 3 PLC ±0.03 4 PLC ±0.002 ANGLES ±3°
			APPROVED RW CHECKED CT
			PIN: SEE TABLE DOCF SD-CB030431
			DRAWN MW
THE DRAWING IS A CONTROLLED DOCUMENT FOR DONGGUAN CONBEONE TECHNOLOGY CO., LTD. IT IS SUBJECT TO CHANGE AND THE SEMPER ENGINEERING CONTROLLING ORGANIZATION SHOULD BE CONTACTED FOR LATEST REVISION.			CUSTOMER COPY
			SIZE A4
			UNIT MM
			SCALE N.T.S
			PAGE 1 OF 1
			REV B

CONBEONE
www.conbeone.com

TITLE: MOLEX 2.54MM PITCH OTS
KK254, DUAL ENDS TYPE B, TYPE BDB